

The technical drawing consists of three orthographic projections of a rectangular plate:

- Top View:** Shows the top surface of the plate. It has overall dimensions of 8.07 inches by 4.65 inches. Key features include:
 - A central horizontal slot with a width of 3.15 inches and a depth of 1.97 inches.
 - A ground hole located 3.01 inches from the left edge and 1.18 inches from the bottom edge, with a diameter of $\varnothing 0.2$.
 - A mounting flange at the bottom right corner with a width of 1.63 inches and a height of 0.08 inches.
 - A small circular feature at the bottom center, 1.95 inches wide and 0.86 inches high.
- Front View:** Shows the front face of the plate. It has overall dimensions of 9.78 inches by 4.13 inches. Key features include:
 - A central circular knockout labeled "(1) 1/2\" NPT Knockout Per Side".
 - A mounting flange at the bottom right corner with a width of 1.89 inches and a height of 1.57 inches.
 - Two M3 screws are shown, spaced 0.39 inches apart, with a total width of 2.05 inches.
- Bottom (Underside) Plate:** Shows the underside of the plate. It has overall dimensions of 4.65 inches by 3.86 inches. Key features include:
 - Four circular knockouts arranged in two rows of two, each labeled "(4) 1/2\" NPT Knockouts".
 - The distance between the centers of the two columns of knockouts is 2.32 inches.
 - The distance between the centers of the two rows of knockouts is 2.09 inches.