

Technical drawing of the Bottom (Underside) Plate, showing three views: Top, Front, and Bottom (Underside).

Top View:

- Overall dimensions: 4.77" (width) x 8.07" (length).
- Top edge features: 0.82" (width of top flange), 3.15" (distance from left edge to center of top flange), 1.97" (distance between top flange centers).
- Right edge features: 4.13" (height of right flange), 8.07" (total length).
- Internal features: Ground hole (Ø 0.2"), 3.01" (distance from left edge to ground hole), 1.18" (distance from ground hole to right edge), 0.08" (thickness of right flange), 1.63" (distance from right edge to center of right flange), 0.86" (width of right flange), 1.95" (distance between right flange centers), 4.65" (total width).

Front View:

- Overall dimensions: 4.13" (height) x 9.78" (length).
- Top edge features: 8.07" (width of top flange), 4.25" (height of top flange).
- Internal features: (1) 1/2" NPT Knockout Per Side, 1.89" (distance from left edge to knockout), 1.57" (distance from knockout to right edge), 0.39" (thickness of top flange), 0.08" (thickness of right flange), 2.05" (distance between right flange centers), 3.86" (total width).

Bottom (Underside) View:

- Overall dimensions: 4.65" (width) x 3.86" (length).
- Top edge features: 1.16" (distance from left edge to center of top flange), 2.32" (distance between top flange centers).
- Right edge features: 2.09" (height of right flange), 0.98" (width of right flange).
- Internal features: (4) 1/2" NPT Knockouts, 3.86" (total width).