

The technical drawing consists of three orthographic projections of a rectangular plate:

- Top View (Left):** Shows the top surface of the plate. The overall dimensions are 9.25 inches by 5.32 inches. Key features include two circular holes at the top, each with a diameter of 0.82 inches, spaced 3.15 inches apart. A ground hole with a diameter of 0.2 inches is located near the bottom center. Other dimensions shown are 4.77 inches, 1.97 inches, 3.01 inches, 1.18 inches, 0.08 inches, 1.63 inches, 1.95 inches, 0.86 inches, and 4.65 inches.
- Front View (Right):** Shows the front edge of the plate. The overall height is 5.32 inches. It shows a single knockout hole with a diameter of 1.89 inches. The distance from the top edge to the center of the knockout is 4.17 inches. The distance from the bottom edge to the center of the knockout is 1.57 inches. The width of the plate is 3.86 inches. There are also dimensions for M3 screws: 0.39 inches, 0.08 inches, and 2.05 inches.
- Bottom (Underside) Plate (Bottom):** Shows the underside of the plate. It features four circular knockouts arranged in a 2x2 grid. The overall dimensions are 4.65 inches by 3.86 inches. The distance between the centers of the knockouts is 2.32 inches horizontally and 2.09 inches vertically. The distance from the edges to the centers of the knockouts is 1.16 inches and 0.98 inches respectively.