

The technical drawing consists of three orthographic projections of a rectangular plate:

- Top View (Left):** Shows the top surface of the plate. The overall dimensions are 9.25 inches by 5.32 inches. It features two circular knockouts at the top, each with a diameter of 0.82 inches. The distance between their centers is 1.97 inches, and they are positioned 3.15 inches from the top edge. A ground hole with a diameter of 0.2 inches is located near the bottom center, 3.01 inches from the left edge and 1.18 inches from the bottom edge. There is also a small feature 0.08 inches wide and 1.63 inches from the bottom edge.
- Front View (Right):** Shows the front face of the plate. The overall dimensions are 10.97 inches by 5.32 inches. It shows a single knockout labeled "(1) 1/2\" NPT Knockout Per Side". The knockout has a diameter of 1.89 inches and is positioned 1.57 inches from the right edge and 4.17 inches from the top edge. There are also M3 threaded holes, one of which is 0.39 inches from the bottom edge and 2.05 inches from the right edge.
- Bottom (Underside) Plate (Bottom):** Shows the underside of the plate. The overall dimensions are 4.65 inches by 3.86 inches. It features four circular knockouts arranged in a 2x2 grid. Each knockout has a diameter of 1.16 inches. The distance between the centers of the knockouts in the horizontal direction is 2.32 inches, and in the vertical direction is 2.09 inches. The knockouts are labeled "(4) 1/2\" NPT".