

Technical drawing of the Bottom (Underside) Plate, showing three views: Top, Front, and Bottom.

Top View: Dimensions include 5.43" (width), 6.14" (height), and 10.08" (depth). Features include three circular knockouts at the top, each with a diameter of 0.2", and a ground hole at the bottom. The distance between the knockouts is 2.95", with 1.12" between each. The distance from the knockouts to the ground hole is 1.23". The ground hole is 1.18" wide and 0.08" deep. The distance from the ground hole to the bottom edge is 1.63". The distance from the bottom edge to the right side is 0.86". The distance from the bottom edge to the left side is 1.95".

Front View: Dimensions include 12.21" (width), 10.08" (height), and 4.25" (depth). Features include a (1) 3/4" NPT knockout per side and an M3 screw. The distance from the knockout to the bottom edge is 1.97". The distance from the knockout to the right side is 1.57". The distance from the knockout to the left side is 2.32". The distance from the knockout to the bottom edge is 0.39". The distance from the knockout to the right side is 0.08". The distance from the knockout to the left side is 4.49".

Bottom View: Dimensions include 5.43" (width), 4.45" (height), and 2.52" (depth). Features include four circular knockouts, each with a diameter of 0.2", and an M3 screw. The distance between the knockouts is 3.23", with 1.1" between each. The distance from the knockouts to the bottom edge is 0.95".

(4) 3/4" NPT Knockouts
Bottom (Underside) Plate