

### Summary

Three-phase delta buck-boost transformer. Steps down 248V to 236V at 7.34 amps continuous output. 3 kVA capacity. NEMA 3R enclosed, cETLus listed, wall mount.

### Product Description

This unit corrects a 248V three phase building supply to 236V delta at the point of use, permanently, without modifying the building's electrical service. Designed for equipment rated 236V that is installed on a 248V system experiencing overvoltage from the utility.

Configured as an open delta autotransformer, the unit handles only the difference between input and output and not the full load. This is why a 7.34-amp buck-boost transformer is significantly smaller and lighter than a 7.34-amp isolation transformer. The encapsulated core construction eliminates audible hum and provides stable thermal performance under continuous duty.

Features a removable wiring compartment door, removable knockout plate, and six NPT knockouts for flexible conduit entry. Surface mounting bracket for easy wall mount installations.



TX-BB-248D-236D-3KVA — NEMA 3R Encapsulated, cETLus Listed

### Specifications

|                     |                              |                       |                              |
|---------------------|------------------------------|-----------------------|------------------------------|
| Phase               | Three Phase Delta (3-PH), AC | Transformer Type      | Buck/Boost                   |
| Capacity            | 3 kVA                        | Configuration         | Encapsulated Autotransformer |
| Primary Voltage     | 248V                         | Primary Termination   | Lead Wires & Terminal Lugs   |
| Primary Amperage    | 6.98A                        | Secondary Termination | Lead Wires & Terminal Lugs   |
| Secondary Voltage   | 236V                         | Termination Access    | (6) ½" NPT Hubs              |
| Secondary Amperage  | 7.34A                        | Winding Material      | Aluminum                     |
| Maximum Primary OCP | 15A                          | Enclosure Material    | Steel                        |
| Frequency           | 50/60 Hz                     | Finish Color          | ANSI 70 Light Grey           |
| Insulation          | 180°C                        | Weight                | 16 lbs                       |
| Temperature Rise    | 115°C                        | Dimensions            | 9.55"-W x 3.86"-D x 8.07"-H  |

### Ratings & Certifications

- Listed for United States
- NEMA 3R Indoor/Outdoor Enclosure
- Built to UL-5085 Standards
- CE Certified
- Listed for Canada
- Epoxy Resin Encapsulated
- RoHS Compliant



### Common Applications

- HVAC & Minisplit
- Loads CNC Machines
- Pump Stations
- Packaging Machines
- Commercial Kitchen Equipment
- Motor Loads
- EV Chargers
- Server Racks & IT Equipment
- Refrigeration & Walk-in
- Coolers Fans & Blowers
- Conveyor Systems
- Overhead Doors

**Important:** Buck-boost transformers applied as autotransformers do not provide circuit isolation and do not create a neutral. Contact us if your application requires isolation or neutral creation.

## Dimensions

Three-phase open delta installation — (2) enclosures required.



## Connection Guide


1. Connect **X4** and **X3** together for each transformer
2. Connect **X2** and **X1** together for each transformer
3. Connect High Voltage **PHASE A** to **X4**, **X3** on transformer A
4. Connect High Voltage **PHASE C** to **X4**, **X3** on transformer B
5. Connect Low Voltage **PHASE A** to **X1**, **X2**, **H4** on transformer A
6. Connect Low Voltage **PHASE C** to **X1**, **X2**, **H4** on transformer B
7. Connect **H2** and **H3** together for each transformer
8. Connect High & Low Voltage **PHASE B** to **H1**
9. Bridge **H1** connections between Transformer A & B

### DIAGRAM H2

#### HIGH VOLTAGE



#### LOW VOLTAGE



sales@sanzosales.com

The image shows two identical grey metal autotransformers from Sanzo Sales. Each unit is a rectangular box with a hinged top and a handle on the side. The front panel features a label with the company logo, model number, and technical specifications. A warning label is also present on the front panel.

**Label Information:**

**SANZO SALES**

**TX-BB-208D-220D-5A**

| Power            | Single Phase | Configuration | Autotransformer |
|------------------|--------------|---------------|-----------------|
| Input Voltage    | 208V         | Max BCP       | 500VA           |
| Output Voltage   | 220V         | Transformer   | 500VA           |
| Maximum Input    | 1.5 kVA      | Max Input     | 1.5 kVA         |
| Max Output Power | 2.5 kVA      | Max Output    | 2.5 kVA         |

**Autotransformer**

**Warning:** Type NEMA 3R for Indoor or Outdoor Use  
 Confirmed to UL 508 - Confirmed to NEMA 3R  
 Stock # TX-BB-208D-220D-5A - 1/2" x 1/2" x 1/2"

**sales@sanzosales.com**



*Base Knockouts — (4) ¾" NPT*



*Side View*



*Rear View — Surface Mount Bracket*



Wiring Compartment — Terminal Leads



*Interior — Epoxy Resin Encapsulated Core*