

■ Summary

112.5 kVA, three-phase general-purpose dry-type isolation transformer. 240V delta primary to 380Y/220 secondary. Aluminum windings, electrostatic shielding, ventilated NEMA 3R enclosure.

■ Product Description

The Sanzo Power TX-DV-112M-3-321304-AL is a 112.5 kVA three-phase dry-type isolation transformer that converts 240V delta power to 380Y/220 for commercial and industrial distribution. The grounded-wye secondary supplies 380V three-phase power for equipment loads and 220V line-to-neutral power through an accessible X0 neutral. The separate primary and secondary windings provide electrical isolation.

Vacuum-pressure-impregnated aluminum windings use a 220°C insulation system with 150°C temperature rise. Natural-convection cooling supports continuous distribution duty.

Front-access terminal lugs simplify field wiring. The bolt-together steel enclosure has replaceable panels, upper hooded vents and continuous mounting runners.



■ Specifications

Phase	Three Phase (3-PH), AC	Transformer Type	Isolation / Distribution
Capacity	112.5 kVA	Duty	Continuous, General Purpose
Primary Voltage	240V delta	Winding Material	Aluminum
Secondary Voltage	380Y/220	Insulation System	220°C
Primary Current	270.6 A	Temperature Rise	150°C
Secondary Current	170.9 A	Cooling	AA / Natural Convection
Frequency	60 Hz	Impregnation	Vacuum Pressure Impregnated
Primary Taps	(2) 2.5% Above, (4) 2.5% Below	Electrostatic Shield	Full Interwinding Shield
Tap Rating	Full Capacity; De-energized	Primary Termination	Terminal Lugs
Primary Connection	Delta / H1, H2, H3	Secondary Termination	Terminal Lugs
Secondary Connection	Wye / X0 Neutral	Termination Access	Front Access Cover
DOE 2016 Minimum	98.74% at 35% Load	Enclosure	NEMA 3R, Ventilated Steel
Voltage Direction	Step-Up	Finish	ANSI 61 Grey Powder Coat
Dimensions L x W x H	32.60" x 31.89" x 35.39"	Mounting	Floor / Continuous Runners

■ Ratings & Certifications

- cETLus - United States & Canada
- UL 1561 / CSA C22.2 No. 47
- DOE 2016 Efficiency
- NEMA 3R Indoor / Outdoor




■ Common Applications

- Commercial Power Distribution
- Industrial Machinery
- HVAC / Mechanical Systems
- Pumps & Process Equipment


Installation: Use the connection diagram for tap selection and field wiring. De-energize before changing taps; maintain ventilation and service access.

Enclosure Outline


LENGTH (L) x WIDTH (W) x HEIGHT (H)




FRONT - UPPER VENTS



SIDE



BOTTOM (UNDERSIDE)



ISOMETRIC - UPRIGHT


Continuous T-top / outward L-floor runners

Capacity	Length (L)	Width (W)	Height (H)
112.5 kVA	32.60"	31.89"	35.39"

Overall dimensions include mounting runners. Length runs front to rear.
Anchor spacing, lifting provisions and conduit openings by approved drawing. Dashed underside lines show upper mounting flange.


Winding & Connection Overview

PRIMARY - 240V delta



DELTA / H PRIMARY

SECONDARY - 380Y/220



WYE / X SECONDARY

H identifies the primary; X identifies the secondary. Purpose-built for the stated voltage direction. Electrostatic shield and enclosure bond to equipment ground. Diagrams show winding topology; final links and phase displacement follow the nameplate.

Tap setting	Primary input	Supply lines
+5%	252V	H1, H2, H3
+2.5%	246V	H1, H2, H3
Nominal	240V	H1, H2, H3
-2.5%	234V	H1, H2, H3
-5%	228V	H1, H2, H3
-7.5%	222V	H1, H2, H3
-10%	216V	H1, H2, H3

Secondary lines	Nominal voltage
X1, X2, X3	380V line-line
X1 / X2 / X3 to X0	219.4V line-neutral

Tap entries are voltage settings, not physical jumper numbers. De-energize before changing taps and set all three phases alike.

Nominal full-load current: primary 270.6 A; secondary 170.9 A. For multiple voltages, current depends on the selected connection. Individual phase or half-winding loading must remain within the nameplate rating.

Use the approved manufacturer connection diagram for installation, grounding, overcurrent protection and terminal torque.

Construction & Installation Details

The continuous mounting runners use a T flange at the enclosure and an outward-only L flange at the floor. Replaceable bolt-on panels allow enclosure repairs without replacing the full housing.

Length (L)	32.60"
Width (W)	31.89"
Height (H)	35.39"
Mounting	Floor / Continuous Runners

Dimensions are L x W x H. Length runs front to rear. Overall height includes the mounting runners.



Electrical Connections

Primary Lines	H1, H2, H3; delta input
Secondary Lines	X1, X2, X3; 380Y/220
Neutral	X0 accessible; 220V line-to-neutral
Shield / Ground	Electrostatic shield bonded to enclosure equipment ground
Tap Operation	(2) 2.5% Above, (4) 2.5% Below; all phases set alike
Connection Access	Front-access cover; terminal lug connections

Service & Installation

Location	Indoor or outdoor; NEMA 3R enclosure
Cooling / Ventilation	Natural convection; keep upper vents unobstructed
Mounting Support	Level, structurally adequate floor or pad
Panel Replacement	Individual bolted panels are replaceable
Grounding	Provide equipment grounding and secondary bonding for the installation
Load Selection	Size for connected kVA, starting duty and phase loading

Primary and secondary windings are electrically isolated. This transformer is purpose-built for the listed voltage direction. Follow the unit nameplate for conductor sizes, terminal torque, overcurrent protection and installation clearances.